# **ICECATCH®** Solid Ambient

ICECATCH<sup>®</sup> Solid Ambient is excellently suited for the transport of temperature-sensitive products in the temperature range of +15°C to +25°C. Thanks to the flexible carrier substrate, this combination cool / warm element is reusable for numerous transport cycles without any loss of quality. One of the unique things about ICEATCH<sup>®</sup> Solid Ambient is the fact that its ingredients are 100% plant-based. ICECATCH<sup>®</sup> Solid Ambient does not contain any mineral oil derivatives or paraffin. What's more, it is non-toxic and can be disposed of in normal household waste. All the materials fulfill the highest standards of robustness and are

#### **Technical Data**

- \* Melting Range +20°C to +22°C
- \* Phase Transition +20 °C to +23°C
- \* Latent Heat: 212 kJ/kg
- \* Spreading of thermal absorption around the +/-1,5°C
- \* range Compatible with PROTECT System Packaging:

## **PROTECT** AMBIENT



completely free of hazardous substances. All the ICECATCH<sup>®</sup> products are approved for use in the pharmaceutical, laboratory, and food industry.

The PA/PE composite film that encloses our cooling elements consists of at least 50% "green" polyethylene. In contrast to conventional plastic made from oil or natural gas, this "green" plastic is made from sugar cane waste materials, offering a novel and sustainable alternative to standard polyethylene.

### The Key Advantages:

- \* Outstanding temperature regulation characteristics between +15°C to +25°C
- \* 100% plant-based ingredients
- \* Non-toxic ingredients
- \* Water Hazard Class WGK 1 (self-classification)
- $\boldsymbol{\star}$  Free of paraffin and mineral oil
- \* Flexible foam core well suited for multiple usages
- $\boldsymbol{\star}$  Maximum form stability during freezing and thawing
- $\boldsymbol{\star}$  Robust PA/PE films, approved for food use
- \* PA/PE composite film is based on at least 50% of the renewable raw material of sugar cane.
- \* Films conform to FDA and EU regulations
- \* Maximum product safety due to our many years of experience in material selection and production technology
- \* Fast preconditioning through the use of specially designed shipping boxes
- \* Increased leakage protection contents are immobilized in the carrier substrate

## List of standard sizes

weight	WxLxH in mm	product name	article no.	pcs./carton	cartons/pallet
800 g	280 x 190 x 30	ICECATCH® Solid Ambient 800 g	19-05002	12	40







an **eutecma** brand